

XA45 / XA40

ULTRA-COMPACT, PROFESSIONAL 4K XA-SERIES CAMCORDER WITH 20X ZOOM LENS

The XA45 / XA40 features a 1/2.3-type CMOS Sensor along with DIGIC DV6 image processor delivering 4K UHD. Full HD image quality is improved thanks to Over Sampling HD Processing. The XA40 features a lens with 20x optical zoom with 29.3mm wide angle.



- Ultra-compact professional 4K UHD camcorder
- 4K 20X optical zoom lens with wide angle
- Infrared recording capability
- Slow and Fast Motion recording
- Lightweight and compact with professional features
- 3G-SDI Interface (XA45 Only)



Over Sampling
HD Processing



INFRARED



Touch Screen

PRODUCT RANGE



XA55 / XA50
(4K UHD)



XA45 / XA40
(4K UHD)



XA15 / XA11 (Full HD)

Canon

Live for the story_

TECHNICAL SPECIFICATIONS

XA45 / XA40

CAMERA

IMAGE SENSOR

Sensor
Filter
Total pixels
Effective pixels
Subject illumination range
Minimum illumination (PAL)

1/2.3-type CMOS
 RGB Primary Colour Filter
 Approx. 21.14MP
 Approx. 8.29 MP (3840 x 2160)
 Approx. 0.3 lx to 100,000 lx
 P Mode: Approx. 4.2 lx (shutter speed 1/25 sec with auto slow shutter On)
 Low Light Mode: Approx. 0.3 lx (shutter speed 1/2 sec.)

LENS

Zoom ratio
Focal length (35mm equivalent)
Minimum focus distance
Aperture
Aperture blades
Filter diameter
Image stabilization system
ND filter

20x optical
 Approx. 29.3 - 601mm Standard IS/IS Off
 10 mm at wide end, 60 cm across entire zooming range
 f/1.8 - 2.8 (AV Priority and Manual Modes)
 8 blades
 58mm
 Optical system (lens shift) + electronic stabilization
 Dynamic, Standard, Powered, Off
 Built-in gradation filter (Auto or Off)

Zoom control

Zoom rockers on body and handle;
 Selectable manual zoom/focus ring on lens;
 Selectable High Speed and Soft Zoom modes available.

Zoom speed

Variable (body rocker only) or Constant speed (body and handle rocker; Fast/Normal/Slow, 16 speed level settings in each)

Focus control

MANUAL: Lens ring and touchscreen point selection (Magnify and Peaking assist functions), Focus Preset.
 AUTOFOCUS: Touchscreen AF point selection, Face Detection and Tracking, Touch and Track, Face Only AF.

Focus System

(Instant AF, Medium AF, Normal AF)

Iris control

Hybrid AF, Normal AF

Digital zoom/Teleconverter

Touchscreen, Auto
 400x Digital Zoom, 2x Digital Teleconverter

IMAGE PROCESSOR

Type
Colour Sampling
Bit depth

DIGIC DV 6
 YCC 4:2:0
 8-bit

RECORDING

Video storage media
Type
Recording time (64GB Card, approx.)

SD/SDHC/SDXC card (2 card slots)
 Class U3 cards recommended
 XF-AVC: 160Mbps: 50 mins / 45Mbps: 185 mins
 MP4: 150Mbps: 55 mins / 35Mbps: 240 mins / 17Mbps: 495 mins

Recording file system
Internal recording format (PAL)

FAT32/exFAT
 XF-AVC: 3840 x 2160 (160Mbps) / 1920 x 1080 (45Mbps)
 MP4: 3840 x 2160 (150Mbps) / 1920 x 1080 (35/17 Mbps)

External recording output (PAL)

HDMI output (Camera mode):
 UHD recording mode: 1920 x 1080 25.00P YCC4:2:2 8-bit
 Full HD recording mode: 1920 x 1080 50.00P/50.00i/25.00P; 1280 x 720 50.00P YCC4:2:2 10-bit

External monitoring
Recording frame rate (PAL)
Slow/Fast motion (PAL)

HDMI (50.00i)
 25.00P (UHD), 50.00P/50.00i/25.00P (Full HD)
 3840 x 2160 / 25.00P: x2, x4, x10, x20, x60, x120, x600, x1200
 1920 x 1080 / 50.00P: x2, x4, x10, x20, x60, x120, x600, x1200
 1920 x 1080 / 25.00P: x0.5

Pre Recording function
Still photos

Yes, 3 seconds
 JPEG up to 3840x2160
 (Still image resolution is dependent on the video resolution)

Photo storage media

SD Card

AUDIO

Recording
Audio control

MPEG-2 AAC-LC (16-bit 2ch) / LPCM (16-bit 4ch)
 Manual/Auto
 Independent 2ch Line/Mic/Mic+48V input;
 Independent level control per channel (-∞ to +18 dB);
 Independent audio limiters (2 ch);
 Input mic trimming
 1KHz, -12dB / -18dB / -20dB / Off
 Auto/On/Off (20dB)
 Yes

Reference tone
Microphone attenuation
Microphone level meter

SYSTEM

MONITORING PANEL

Type
Size
Waveform Monitor
Focus Assist
Peaking
Zebra
Markers

Capacitive LCD touch panel
 3.0-inch (7.5 cm, approx. 460,000 dots)
 No
 Peaking / Magnify
 Selectable Peaking Colour: Red / Blue / Yellow
 70% or 100% reference level
 Grid (white/grey) and Level (white/grey)

VIEWFINDER

Size
Correction lens

0.24-inch, approx. 1.56 million dots
 +2.0 to -5 dioptre

INPUTS/OUTPUTS

Audio input

XLR 3-pin jack (x2) with 48V phantom power, Line and Mic options on detachable handle,
 3.5mm microphone input jack (Supply Voltage 2.4V DC), Built-in Mic

Headphone output

3.5mm stereo mini jack

HDMI output

HDMI™ mini connector

USB

Mini-B, Hi-Speed USB, PTP class supported

SDI output

XA45: 3G-SDI with BNC connector
 XA40: No

Time code

Superimposed on HDMI output signal (Camera Mode only)

Genlock

No

LAN

No

AV terminal

No

DC input

3.4mm jack

Remote Control Terminal

2.5mm mini jack

SHOOTING FUNCTIONS

EXPOSURE

Exposure metering

Centre-weighted average or segment evaluative (determined by shooting mode)
 No metering: Fireworks mode, Fixed exposure (1/50 sec.)

Exposure compensation

Highlight AE, Exposure lock, Auto backlight compensation, Exposure compensation amount shown as ±3 when locked (±12 increments) or ±2 in AUTO (±8 increments).

Exposure Lock

Yes.

Auto Gain Control setting

Auto / Manual

Auto Gain Control limit

0 - 24dB (1dB increments)

SHUTTER SPEED

Control modes

Auto, P, Tv, Manual

Shutter speed

1/6 - 1/2000 sec
 (1/2 - 1/500 sec in Low Light mode)

Slow Shutter (SLS)

50.00P:
 Auto slow shutter On: 1/25 to 1/500 sec.
 Auto slow shutter Off: 1/50 to 1/500 sec.

25.00P:
 Auto slow shutter On: 1/12.5* to 1/500 sec.
 (*Display is 1/12)

Auto slow shutter Off: 1/25 to 1/500 sec.

Clear Scan

No

WHITE BALANCE

Auto

Yes

Preset

Daylight (Approx. 5,600K), Tungsten (Approx. 3,200K)

Manual setting

Colour Temperature range: 2,000-15,000K
 Default value for Set 1 and Set 2: 5,600K



TECHNICAL SPECIFICATIONS

XA45 / XA40

SHOOTING MODES

| | |
|-------------------------------|---|
| Program AE | AUTO Mode Manual Mode: P, Tv, Av, M (manual exposure), SCN (Portrait, Sports, Snow, Beach, Sunset, Night, Low Light, Spotlight, Fireworks) |
| Infrared shooting mode | Yes (green or white) |
| Built-in IR lamp | Yes, in detachable Handle Unit. Wavelength: 850nm (near-Infrared) |
| Look settings | Standard (Adjustment: Sharpness, Contrast, Colour Depth) |

WI-FI & GPS SPECIFICATIONS

| | |
|---|--|
| Wi-Fi | No |
| GPS Information (Optional Accessory) | Location (Latitude/Longitude/Altitude), Coordinated Universal Time (UTC), Satellite reception. (requires the optional GPS Receiver GP-E2) |

MISCELLANEOUS

| | |
|---------------------------|---|
| Tally lamp | Yes, in detachable Handle Unit |
| Colour Bars (PAL) | Yes. SMPTE or EBU, with 1KHz Tone |
| Accessory shoe | Yes (cold shoe) |
| Assignable buttons | 5 assignable Buttons: Assignable to (AF/MF) / Face Only AF / Magnification / BLC Always On / Powered IS / Auto Acquire WB / WB Priority / IR Light / Pre REC / Review Recording / PHOTO / Monitor Channels / Menu / Off |
| Custom dial | Tv / Av / M / AGC Limit / Exposure Compensation / Off |

TIME CODE

| | |
|------------------------|--|
| Count-up system | Regen / Rec Run / Free Run / Preset (Non-Drop Frame) |
| Time Code out | Via HDMI out. Superimposed on output, Camera Mode only |

ACCESSORIES

| | |
|--|---|
| Supplied | Lens hood with barrier, Mic holder unit, Handle Unit HDU-1, Battery Pack BP-820, Compact Power Adapter CA-570, AC Cable, Ferrite core, Lens Cap |
| Optional (Includes items not currently on sale) | Canon Battery Pack BP-820/BP-828, Canon Compact Power Adapter CA-570 (included with camera), Canon Battery Charger CG-800E/CG-800, Canon HDMI cable HTC-100/HTC-100S, Canon Tele Converter TL-H58, Canon Wide Attachment WA-H58, Canon Soft Carrying Case SC-1000/SC-2000, Canon Shoulder Strap SS-600/SS-650, Wrist Strap WS-20, Canon PROTECT Filter 58mm, Canon ND4-L Filter 58mm, Canon ND8-L Filter 58mm, Canon GPS Receiver GP-E2, Canon Remote Controller RC-V100, Canon Battery Video Light VL-10Li/VL-10LiII, Canon Battery Pack BP-900 series (for VL-10Li/VL-10LiII), Canon Compact Power Adapter CA-910/920/930 (for charging BP-900 series), Canon Interface Cable IFC-300PCU/S / IFC-400PCU |

BATTERY

| | |
|--|---|
| Battery Pack | Canon Battery Pack BP-820 (supplied), BP-828 (optional) |
| Power Consumption (recording) | XF-AVC: UHD/160Mbps: Approx. 4.1W (25.00P) MP4: UHD/150Mbps: Approx. 4.1W (25.00P) |
| Continuous Recording Time (approx.) | XF-AVC: UHD/160Mbps/25.00P: 175 mins (BP-820) / 270 mins (BP-828) FHD/45Mbps/50.00P: 170 mins (BP-820) / 265 mins (BP-828) MP4: UHD/150Mbps/25.00p: 175 mins (BP-820) / 270 Mins (BP-828) FHD/35Mbps/50.00p: 175 mins (BP-820) / 270 Mins (BP-828) |

SIZE AND WEIGHT

| | |
|------------------------------------|---|
| Dimensions | Approx. 109 x 84 x 182 mm (main body only) Approx. 131 x 180 x 231 mm (Including lens hood, BP-820, mic holder unit, and handle unit) |
| Weight (camera only) | XA45: Approx. 740g XA40: Approx. 730g |
| Weight (fully equipped) | XA45: Approx. 1130g XA40: Approx. 1120g (Includes lens hood, mic holder unit, handle unit, BP-820, and 1 memory card) |
| Operating temperature range | -5 to +45°C, 60% relative humidity 0°C to +40°C, 85% relative humidity |

Disclaimers

All specifications are subject to change without notice
Specification given for PAL Version

Live for the story_

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2021

ULTRA-COMPACT, PROFESSIONAL 4K XA-SERIES CAMCORDER WITH 20X ZOOM LENS

XA45 / XA40

The XA45 / XA40 features a 1/2.3-type CMOS Sensor along with DIGIC DV6 image processor delivering 4K UHD. Full HD image quality is improved thanks to Over Sampling HD Processing. The XA40 features a lens with 20x optical zoom with 29.3mm wide angle.

Sales Start Date: February 2021



PRODUCT DETAILS:

| Product Name | Mercury Code | EAN Code | Recommended Retail Price |
|--------------|--------------|---------------|--------------------------|
| XA45 | 3665C003AA | 4549292139624 | <Please fill in RRP> |
| XA40 | 3666C003AA | 4549292139648 | <Please fill in RRP> |

OPTIONAL ACCESSORIES

| Accessories | Mercury Code | EAN Code | Recommended Retail Price |
|-----------------------------|--------------|---------------|--------------------------|
| Battery BP-820 | 8597B002AA | 4960999984490 | <Please fill in RRP> |
| Battery BP-828 | 8598B002AA | 4960999984520 | <Please fill in RRP> |
| Battery Charger C.G-800 | 2590B003AA | 4960999612188 | <Please fill in RRP> |
| Battery Charger C.G-800E(B) | 2590B006AA | 4960999610573 | <Please fill in RRP> |
| Remote Controller RC-V100 | 9660B001AB | 4549292014013 | <Please fill in RRP> |
| Video Light VL-10Li II | 1729B001AA | 4960999408316 | <Please fill in RRP> |
| Shoulder Strap SS-600 | 3122A001BA | 4960999605913 | <Please fill in RRP> |
| Shoulder Strap SS-650 | 3123A001BA | 4960999605951 | <Please fill in RRP> |
| Wrist Strap WS-20 | 3118A001BA | 4960999600314 | <Please fill in RRP> |
| Soft carrying case SC-2000 | 9389A001AA | 4960999209852 | <Please fill in RRP> |
| HDMI cable HTC-100 | 2384B001AA | 4960999530383 | <Please fill in RRP> |
| GPS receiver GP-E2 | 6363B001AA | 4960999848358 | <Please fill in RRP> |
| TL-H58 | 3573B001AA | 4549292105391 | <Please fill in RRP> |
| WA-H58 | 8640B001AA | 4549292105407 | <Please fill in RRP> |

The Canon logo, consisting of the word 'Canon' in a bold, red, sans-serif font.

Live for the story_

ULTRA-COMPACT, PROFESSIONAL 4K XA-SERIES CAMCORDER WITH 20X ZOOM LENS

XA45 / XA40

The XA45 / XA40 features a 1/2.3-type CMOS Sensor along with DIGIC DV6 image processor delivering 4K UHD. Full HD image quality is improved thanks to Over Sampling HD Processing. The XA40 features a lens with 20x optical zoom with 29.3mm wide angle.



MEASUREMENT / LOGISTIC INFORMATION:

| Product Name | Mercury Code | Pack type | Pack description | Quantity per pack | Length (mm) | Width (mm) | Height (mm) | Gross Weight (kg) |
|--------------|--------------------------|-----------|--------------------|-------------------|-------------|------------|-------------|-------------------|
| XA45 / XA40 | 3665C003AA 3666C003AA | EA | Each | 1 | 279 | 274 | 218 | 2.35 |
| | | CT | Carton | 2 | 561 | 292 | 239 | 5.33 |
| | | EP | Euro Pallet | 32 | 120 | 80 | 110.6 | 95.3 |
| | | | Layers per Pallet | 4 | | | | |
| | | | Cartons per Layer | 4 | | | | |
| | | | Products per layer | 8 | | | | |
| | | | | | | | | |

What's in the box?

- XA45 / XA40 body
- Lens cap
- Lens hood with lens barrier
- Microphone Holder Unit
- Screws for Microphone Holder Unit
- Handle Unit HDU-1
- CA-570 Compact Power Adapter
- Ferrite core
- AC Cable EU
- BP-820 Battery Pack
- Printed Materials

Canon

Live for the story_